

**DOW CORNING DO BRASIL LTDA
MATERIAL SAFETY DATA SHEET
(MSDS)**

DOW CORNING(R) CONTRACTORS PROFESSIONAL SEALANT, BLACK

1. PRODUCT AND COMPANY IDENTIFICATION

Dow Corning Do Brasil Ltda Rod. Jornalista Francisco Aguirra Proença, s/nº - Km 8,5 Bairro: Chácaras Assay CEP 13186-903 Hortolândia/SP Brasil	Emergency Telephone Number 24 hr: (019)3887-9600 Emergency Telephone Number 24 hr: 0800-0111944 PROQUIMICA (ABIQUIM) 24hr: 0800-0118270 SOS COTEC: 0800-111767 SOS COTEC: 0800-7711767 SOS COTEC: 0800-7071767
Dow Corning Corporation South Saginaw Road Midland, Michigan 48686	24 Hour Emergency Telephone: (989) 496-5900 Customer Service: (989) 496-6000

MSDS No.: 04114416 Revision Date: 2012/10/29

NFPA Profile: Health 0 Flammability 1 Instability/Reactivity 0

Note: NFPA = National Fire Protection Association

2. COMPOSITION/INFORMATION ON INGREDIENTS

Pure Substance
None present. This is not a hazardous material as defined in the OSHA Hazard Communication Standard.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Generic Description: Silicone Sealant
Physical Form: Paste
Color: Off-White
Odor: Odorless

There are no components with workplace exposure limits.

+++++

POTENTIAL HEALTH EFFECTS

Acute Effects

Eye: Direct contact may cause temporary redness and discomfort.

DOW CORNING DO BRASIL LTDA MATERIAL SAFETY DATA SHEET (MSDS)

Page: 2 of 8
Version: 1.0
Revision Date: 2012/10/29

DOW CORNING(R) CONTRACTORS PROFESSIONAL SEALANT, BLACK

Skin: No significant irritation expected from a single short-term exposure.

Inhalation: No significant effects expected from a single short-term exposure.

Oral: Low ingestion hazard in normal use.

Prolonged/Repeated Exposure Effects

Skin: No known applicable information.

Inhalation: No known applicable information.

Oral: No known applicable information.

Signs and Symptoms of Overexposure

No known applicable information.

Medical Conditions Aggravated by Exposure

No known applicable information.

The above listed potential effects of overexposure are based on actual data, results of studies performed upon similar compositions, component data and/or expert review of the product. Please refer to Section 11 for the detailed toxicology information.

4. FIRST AID MEASURES

Eye: If irritation occurs, flush eye(s) with lukewarm gently flowing water for 5 minutes. Obtain medical attention.

Skin: No health effects expected. If irritation does occur flush with lukewarm, gently flowing water for 5 minutes. If irritation persists, obtain medical advice.

Inhalation: If symptoms are experienced remove source of contamination or move victim to fresh air. If irritation persists, obtain medical advice.

Oral: If irritation or discomfort occur, obtain medical advice.

Notes to Physician: Treat according to person's condition and specifics of exposure.

5. FIRE FIGHTING MEASURES

Flash Point: Not applicable.

**DOW CORNING DO BRASIL LTDA
MATERIAL SAFETY DATA SHEET
(MSDS)**Page: 3 of 8
Version: 1.0
Revision Date: 2012/10/29**DOW CORNING(R) CONTRACTORS PROFESSIONAL SEALANT, BLACK**

Autoignition Temperature: Not determined.

Flammability Limits in Air: Not determined.

Extinguishing Media: On large fires use dry chemical, foam or water spray. On small fires use carbon dioxide (CO₂), dry chemical or water spray. Water can be used to cool fire exposed containers.

Fire Fighting Measures: Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.

Unusual Fire Hazards: None.

6. ACCIDENTAL RELEASE MEASURES

Containment/Clean up: Observe all personal protection equipment recommendations described in Sections 5 and 8. Wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard. Final cleaning may require use of steam, solvents or detergents. Dispose of saturated absorbant or cleaning materials appropriately, since spontaneous heating may occur. Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

Note: See Section 8 for Personal Protective Equipment for Spills. Refer to Section 1 to obtain telephone numbers, if additional information is required.

7. HANDLING AND STORAGE

Use with adequate ventilation. Avoid eye contact.

Use reasonable care and store away from oxidizing materials. This material in its finely divided form presents an explosion hazard. Follow NFPA 654 (for chemical dusts) or 484 (for metal dusts) as appropriate for managing dust hazards to minimize secondary explosion potential.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**Component Exposure Limits**

There are no components with workplace exposure limits.

Engineering Controls

Local Ventilation: None should be needed.

**DOW CORNING DO BRASIL LTDA
MATERIAL SAFETY DATA SHEET
(MSDS)**Page: 4 of 8
Version: 1.0
Revision Date: 2012/10/29**DOW CORNING(R) CONTRACTORS PROFESSIONAL SEALANT, BLACK**

General Ventilation: Recommended.

Personal Protective Equipment for Routine Handling

Eyes: Use proper protection - safety glasses as a minimum.

Skin: Washing at mealtime and end of shift is adequate.

Suitable Gloves: Handle in accordance with good industrial hygiene and safety practices.

Inhalation: No respiratory protection should be needed.

Suitable Respirator: None should be needed.

Personal Protective Equipment for Spills

Eyes: Use proper protection - safety glasses as a minimum.

Skin: Washing at mealtime and end of shift is adequate.

Inhalation/Suitable
Respirator: No respiratory protection should be needed.

Precautionary Measures: Avoid eye contact. Use reasonable care.

Note: These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Form: Paste

Color: Off-White

Odor: Odorless

Specific Gravity @ 25°C: 1.51

Viscosity: Not determined.

Freezing/Melting Point: Not determined.

Boiling Point: Not determined.

Vapor Pressure @ 25°C: Not determined.

Vapor Density: Not determined.

Solubility in Water: Not determined.

pH: Not determined.

Volatile Content: Not determined.

Flash Point: Not applicable.

Autoignition Temperature: Not determined.

Flammability Limits in Air: Not determined.

Note: The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing specifications.

**DOW CORNING DO BRASIL LTDA
MATERIAL SAFETY DATA SHEET
(MSDS)**

Page: 5 of 8
Version: 1.0
Revision Date: 2012/10/29

DOW CORNING(R) CONTRACTORS PROFESSIONAL SEALANT, BLACK

10. STABILITY AND REACTIVITY

Chemical Stability: Stable.

Hazardous Polymerization: Hazardous polymerization will not occur.

Conditions to Avoid: None.

Materials to Avoid: Oxidizing material can cause a reaction.

Hazardous Decomposition Products

Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Carbon oxides and traces of incompletely burned carbon compounds. Metal oxides. Formaldehyde. Silicon dioxide. Quartz.

11. TOXICOLOGICAL INFORMATION

Special Hazard Information on Components

No known applicable information.

12. ECOLOGICAL INFORMATION

Environmental Fate and Distribution

Complete information is not yet available.

Environmental Effects

Complete information is not yet available.

Fate and Effects in Waste Water Treatment Plants

Complete information is not yet available.

Ecotoxicity Classification Criteria

Hazard Parameters (LC50 or EC50)	High	Medium	Low
Acute Aquatic Toxicity (mg/L)	<=1	>1 and <=100	>100
Acute Terrestrial Toxicity	<=100	>100 and <= 2000	>2000

This table is adapted from "Environmental Toxicology and Risk Assessment", ASTM STP 1179, p.34, 1993.

This table can be used to classify the ecotoxicity of this product when ecotoxicity data is listed above. Please read the other information presented in the section concerning the overall ecological safety of this material.

**DOW CORNING DO BRASIL LTDA
MATERIAL SAFETY DATA SHEET
(MSDS)**Page: 6 of 8
Version: 1.0
Revision Date: 2012/10/29**DOW CORNING(R) CONTRACTORS PROFESSIONAL SEALANT, BLACK****13. DISPOSAL CONSIDERATIONS****RCRA Hazard Class (40 CFR 261)**

When a decision is made to discard this material, as received, is it classified as a hazardous waste? Complete information is not yet available.

State or local laws may impose additional regulatory requirements regarding disposal. Refer to Section 1 to obtain telephone numbers, if additional information is required.

14. TRANSPORT INFORMATION**Brazil Land Transportation (Land Transportation National Agency - ANTT Resolutions 420/04, 701/04, 1644/06, 2657/08, 3383/10 and 3632/11).**

Not subject to local road regulations.

Ocean Shipment (IMDG)

Not subject to IMDG code.

Air Shipment (IATA)

Not subject to IATA regulations.

Refer to Section 1 to obtain telephone numbers, if additional information is required.

15. REGULATORY INFORMATION

Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA Status: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

EPA SARA Title III Chemical Listings**Section 302 Extremely Hazardous Substances (40 CFR 355):**

None.

Section 304 CERCLA Hazardous Substances (40 CFR 302):

None.

Section 311/312 Hazard Class (40 CFR 370):

**DOW CORNING DO BRASIL LTDA
MATERIAL SAFETY DATA SHEET
(MSDS)**

Page: 7 of 8
Version: 1.0
Revision Date: 2012/10/29

DOW CORNING(R) CONTRACTORS PROFESSIONAL SEALANT, BLACK

Acute: No
Chronic: No
Fire: No
Pressure: No
Reactive: No

Section 313 Toxic Chemicals (40 CFR 372):

None present or none present in regulated quantities.
Note: Chemicals are listed under the 313 Toxic Chemicals section only if they meet or exceed a reporting threshold.

Supplemental State Compliance Information

California

Warning: This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm.

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>	
67-56-1	<0.1000	Methyl alcohol	Developmental toxin.

New Jersey

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
471-34-1	40.0 - 60.0	Calcium carbonate
70131-67-8	15.0 - 35.0	Dimethyl siloxane, hydroxy-terminated
63148-62-9	7.0 - 13.0	Polydimethylsiloxane
14808-60-7	<1.0	Quartz

Pennsylvania

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
471-34-1	40.0 - 60.0	Calcium carbonate
70131-67-8	15.0 - 35.0	Dimethyl siloxane, hydroxy-terminated
63148-62-9	7.0 - 13.0	Polydimethylsiloxane

**DOW CORNING DO BRASIL LTDA
MATERIAL SAFETY DATA SHEET
(MSDS)**

Page: 8 of 8

Version: 1.0

Revision Date: 2012/10/29

DOW CORNING(R) CONTRACTORS PROFESSIONAL SEALANT, BLACK**16. OTHER INFORMATION**

Prepared by: Dow Corning Corporation

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

(R) indicates Registered Trademark